



**YOU MUST READ THIS QUICK
GUIDE BEFORE YOU START!**



For FAQs and more information, please visit:
xprousa.com/pages/support

How to adjust speed limiter on your ATV?

For your safety, a speed restriction has been set in place for this ATV. If you want to increase the maximum speed, simply loosen the bolt of the speed governor on the right handlebar. For instruction on how to adjust the bolt, please view our video for more details.

Loosen the bolt



① Find speed limit screw



② Remove white glue



③ Loosen the bolt



For FAQs and more information, please visit:
xprousa.com/pages/support

STOP! MUST READ

PLEASE REMEMBER TO VIEW THE ASSEMBLY VIDEO BEFORE PROCEEDING!

For Assembly video and Troubleshooting Tips, please visit below link or scan the QR code below with your mobile phone. tinyurl.com/xpro118



We want to thank you for choosing us. We are committed to making sure you are happy with your purchase, so we would love to hear your experience with your new product!

Please give us a chance to make it right before you leave negative feedback. If you are not satisfied with your experience, we will do whatever needs to be done to make it right. Please visit our website for assembly guide, product maintenance, product support, replacement parts, and any other questions or concerns.

If you are missing a piece or there is shipping damage, need instructions or require help with other issues, please reach out to our customer care team by e-mailing us at support@motopro.freshdesk.com.

If you have any question, please send us a video no less than 30 seconds showing the problem so that we can forward it to the manufacturer for tech support. We would also like to offer an additional 1 month warranty after receiving your video.

You have to option to send us your video:

- 1. Message us the video attachment to phone number (469) 815-8600.**
- 2. Email us the video.**

Your engagement and support are our greatest motivation to provide the best customer service possible. We highly appreciate your cooperation. Hope you have a pleasant shopping experience.

Please register your warranty service by visiting our official website directly or scan the QR code below by mobile phone. Thank you and we are always here to help you!



Tips

Upon receiving your vehicle (and after reviewing the video) we recommend that you heed the following tips:

1. For your safety, a **speed restriction** has been set in place for this ATV. If you want to increase the maximum speed, simply loosen the bolt of the speed governor on the right handlebar. For instruction on how to adjust the bolt, please view our video for more details.
2. Perform your first **oil change** by replacing the Engine oil with 10W40 motor oil prior to starting. Always remember to check the oil level on your dipstick after adding new oil to see if the oil is at the right level. It is better to use fresh unleaded gasoline. If your vehicle has been unused for an extended period of time, remember to replace the gasoline before use.
3. Always remember to check and **tighten your bolts** before you ride for safety. You can also use a little Loctite Threadlocker to reinforce the loose screw.
4. For vehicle with **remote control**, you need to press the unlock button on the controller first.
5. Remember to **connect and double check the battery wires**. The battery will take charge itself during riding. Disconnect the battery if you will not intend to use the vehicle for an extended period of time.
6. Make sure the **kill switch** on the left handle bar is OFF. If the kill switch is engaged, the unit will not start.
7. Make sure **ignition key** is turned to the ON position. If the ignition key is in the OFF position, the unit will not start.
8. Make sure the **choke** on the carburetor is in the UP position when you try to start this bike. Turn the choke off after the engine gets warmed up enough.
9. Please fully release the **throttle** before you hold brake lever. This will effectively reduce the braking distance and make your ride safer.
10. Always make sure the front and rear chain sprockets are on a straight line. And then adjust your **chain** to proper tension if necessary.

If you have any questions or issues, just feel free to contact us, we are always here to help. Thank you!